according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : BASIC WIT-PM 200 - 300 ML (A)

Product code : 5918242300 (A)

Unique Formula Identifier

(UFI)

4EJG-504Q-700R-RPSS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Adhesives

stance/Mixture Professional use product

Recommended restrictions

on use

: Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

isi@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 - 84463

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/

spray

P273 Avoid release to the environment.

P280 Wear protective gloves.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P362 + P364 Take off contaminated clothing and wash it

before reuse.

Disposal:

P501 Dispose of contents/ container to an approved

waste disposal plant.

Hazardous components which must be listed on the label:

Tetramethylene dimethacrylate

Methacrylic acid, monoester with propane-1,2-diol

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No. Index-No.		(% w/w)
	Registration number		
Tetramethylene dimethacrylate	2082-81-7 218-218-1	Skin Sens. 1B; H317	>= 10 - < 20
	607-766-00-0 01-2119967415-30		
Vinyltoluene	25013-15-4 246-562-2 01-2119622074-50	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 STOT SE 3; H335 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 2; H411 M-Factor (Acute aquatic toxicity): 1 Acute toxicity estimate Acute oral toxicity:	>= 2,5 - < 10
		500 mg/kg	
Quartz (SiO2)	14808-60-7 238-878-4	STOT RE 1; H372 (Lungs)	>= 1 - < 10
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1 248-666-3 01-2119490226-37	Eye Irrit. 2; H319 Skin Sens. 1; H317 STOT SE 3; H335	>= 1 - < 10
1-Isopropyl-2,2- dimethyltrimethylene diisobutyrate	6846-50-0 229-934-9 01-2119451093-47	Repr. 2; H361d Aquatic Chronic 3; H412	>= 0,25 - < 1
Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol	Not Assigned 01-2119979579-10	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 0,25 - < 1
		Acute toxicity esti- mate	
4.41 (n.40) dimina) dinama 2.41	20000 40 2	Acute oral toxicity: 619 mg/kg	0.4 0.05
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	Acute Tox. 2; H300	>= 0,1 - < 0,25

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

	254-075-1 01-2119980937-17	Eye Irrit. 2; H319 Aquatic Chronic 3; H412	
1,4-Naphthoquinone	130-15-4 204-977-6 01-2120760462-57	Acute Tox. 3; H301 Acute Tox. 2; H330 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT SE 3; H335 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 Acute toxicity estimate Acute oral toxicity:	>= 0,025 - < 0,1
		124 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled : If inhaled, remove to fresh air.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides Silicon oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.
Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing dust, fume, gas, mist, vapours or spray.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Keep in properly labelled containers. Store in accordance with

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Date of last issue: 27.06.2024 Version Revision Date: SDS Number: 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

the particular national regulations. areas and containers

Do not store with the following product types: Advice on common storage

Strong oxidizing agents

Storage class (TRGS 510) : 11

Recommended storage tem- : 5 - 25 °C

perature

7.3 Specific end use(s)

Specific use(s) No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis		
		of exposure)				
Vinyltoluene	Vinyltoluene 25013-15-4		20 ppm	DE TRGS		
			98 mg/m3	900		
	Peak-limit: ex	cursion factor (categ	ory): 2;(I)			
		MAK	20 ppm	DE DFG MAK		
			98 mg/m3			
	Peak-limit: ex	cursion factor (categ	ory): 2; I			
	Further inform	nation: Either there a	re no data for an assessmen	t of damage to		
			velopmental neurotoxicity, or			
	available data are not sufficient for classification in one of the groups A - C					
Silicon, amorphous	112945-52-	AGW (Inhalable	4 mg/m3	DE TRGS		
	5	fraction)	(Silica)	900		
	Further information: When there is compliance with the OEL and biological					
	tolerance values, there is no risk of harming the unborn child					
	MAK (measured 0,02 mg/m3 DE D					
		as the alveolate				
		fraction)				
	Peak-limit: excursion factor (category): 8; II					
	Further information: Damage to the embryo or foetus is unlikely when the					
	MAK value or the BAT value is observed					
Quartz (SiO2)	14808-60-7	TWA (Respirable	0,1 mg/m3	2004/37/EC		
		dust)				
	Further information: Carcinogens or mutagens					

This substance(s) is not bioavailable and therefore does not contribute to a dust inhalation hazard.

Quartz (SiO2)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Substance name	End Use	Exposure routes	Potential health effects	Value
Tetramethylene di- methacrylate	Workers	Inhalation	Long-term systemic effects	14,5 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,3 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
Methacrylic acid, monoester with propane- 1,2-diol	Workers	Inhalation	Long-term systemic effects	14,7 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,2 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,35 mg/m3
	Consumers	Skin contact	Long-term systemic effects	2,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	2,5 mg/kg bw/day
1-Isopropyl-2,2- dimethyltrimethylene diisobutyrate	Workers	Inhalation	Long-term systemic effects	17,62 mg/m3
•	Workers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4,35 mg/m3
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
Reaction mass of 2- {[2-(2- hydroxyeth- oxy)ethyl](4- methylphenyl)amino}e thanol and 2,2'-[(4- methylphenyl)imino]di ethanol	Workers	Inhalation	Long-term systemic effects	9,8 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,4 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	2,9 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,83 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,83 mg/kg bw/day
1,1'-(p- tolylimino)dipropan-2-	Workers	Inhalation	Long-term systemic effects	2 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

lol				1
5.	Workers	Skin contact	Long-term systemic effects	0,6 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,4 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,3 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,3 mg/kg bw/day
Vinyltoluene	Workers	Inhalation	Long-term systemic effects	5,82 mg/m3
	Workers	Skin contact	Long-term systemic effects	1,65 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,03 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,595 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,595 mg/kg bw/day
1,4-Naphthoquinone	Workers	Inhalation	Long-term systemic effects	0,033 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
Tetramethylene dimethacrylate	Fresh water	0,087 mg/l
	Marine water	0,009 mg/l
	Intermittent use/release	0,098 mg/l
	Sewage treatment plant	20 mg/l
	Fresh water sediment	3,12 mg/kg
	Marine sediment	0,312 mg/kg
	Soil	0,573 mg/kg
Methacrylic acid, monoester with propane-1,2-diol	Fresh water	0,904 mg/l
	Freshwater - intermittent	0,972 mg/l
	Marine water	0,09 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	6,28 mg/kg dry weight (d.w.)
	Marine sediment	6,28 mg/kg dry weight (d.w.)
	Soil	0,727 mg/kg dry weight (d.w.)
1-Isopropyl-2,2- dimethyltrimethylene diisobutyr- ate	Fresh water	0,014 mg/l
	Marine water	0,001 mg/l
	Sewage treatment plant	3 mg/l
	Fresh water sediment	5,29 mg/kg dry weight (d.w.)
	Marine sediment	0,529 mg/kg dry weight (d.w.)
	Soil	1,05 mg/kg dry

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

		weight (d.w.)
	Oral (Secondary Poisoning)	83,3 mg/kg food
Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol	Fresh water	0,048 mg/l
71 7/	Freshwater - intermittent	0,48 mg/l
	Marine water	0,005 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	1,2 mg/kg dry weight (d.w.)
	Marine sediment	0,12 mg/kg dry weight (d.w.)
	Soil	0,21 mg/kg dry weight (d.w.)
1,1'-(p-tolylimino)dipropan-2-ol	Fresh water	0,017 mg/l
	Marine water	0,0017 mg/l
	Intermittent use/release	0,17 mg/l
	Sewage treatment plant	199,5 mg/l
	Fresh water sediment	0,0782 mg/kg
	Marine sediment	0,00782 mg/kg
	Soil	0,005 mg/kg
Vinyltoluene	Fresh water	0,319 μg/l
	Freshwater - intermittent	3,19 µg/l
	Marine water	0,0319 µg/l
	Marine water - intermittent	0,319 μg/l
	Sewage treatment plant	5,92 mg/l
	Fresh water sediment	0,032 mg/kg dry weight (d.w.)
	Marine sediment	0,0032 mg/kg dry weight (d.w.)
	Soil	0,00621 mg/kg dry weight (d.w.)
1,4-Naphthoquinone	Fresh water	26,1 mg/l
, , ,	Fresh water sediment	321 mg/kg dry weight (d.w.)
	Marine water	2,61 mg/l
	Marine sediment	32,1 mg/kg dry weight (d.w.)
	Sewage treatment plant	0,172 mg/l
	Soil	49 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:

Safety glasses

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Equipment should conform to DIN EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : > 0,2 mm

Directive : Equipment should conform to DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DIN EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : beige

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Flash point : Not applicable

Auto-ignition temperature : Not applicable

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : Not applicable

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : Not applicable

Density : 1,72 g/cm³ (20 °C)

Relative vapour density : Not applicable

Particle characteristics

Particle size : No data available

9.2 Other information

Explosives : Not explosive

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of : Skin contact exposure Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

Tetramethylene dimethacrylate:

Acute oral toxicity : LD50 (Rat): 10.066 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Vinyltoluene:

Acute oral toxicity : LD50 (Mouse): 800 - 1.182 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,02 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Quartz (SiO2):

Acute oral toxicity : LD50 (Rat): > 22.500 mg/kg

Methacrylic acid, monoester with propane-1,2-diol:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity : LD50 (Rabbit, male): > 5.000 mg/kg

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 425

Assessment: The substance or mixture has no acute oral tox-

icity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Acute oral toxicity : LD50 (Rat, male): 619 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

1,1'-(p-tolylimino)dipropan-2-ol:

Acute oral toxicity : LD50 (Rat): > 25 - 200 mg/kg

Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

1,4-Naphthoquinone:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Acute oral toxicity : LD50 (Rat): 124 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,046 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Species : Rabbit

Result : No skin irritation

Vinyltoluene:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : Skin irritation

Quartz (SiO2):

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rabbit

Result : No skin irritation

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Result : Skin irritation

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version **Revision Date:** SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

1,1'-(p-tolylimino)dipropan-2-ol:

Species Rabbit

Method **OECD Test Guideline 404**

Result No skin irritation

1,4-Naphthoquinone:

Result Corrosive after 1 to 4 hours of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Species

Result No eye irritation

Quartz (SiO2):

Species Rabbit

Method **OECD Test Guideline 405**

Result No eye irritation

Remarks Based on data from similar materials

Methacrylic acid, monoester with propane-1,2-diol:

Species Rabbit

Result Irritation to eyes, reversing within 21 days

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species Rabbit

Method **OECD Test Guideline 405**

Result No eye irritation

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-

methylphenyl)imino]diethanol:

Species Rabbit

Method **OECD Test Guideline 405** Result Irreversible effects on the eye

1,1'-(p-tolylimino)dipropan-2-ol:

Species Rabbit

Method **OECD Test Guideline 405**

Result Irritation to eyes, reversing within 7 days

1,4-Naphthoquinone:

Result Irreversible effects on the eye

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Assessment : Probability or evidence of low to moderate skin sensitisation

rate in humans

Vinyltoluene:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Methacrylic acid, monoester with propane-1,2-diol:

Exposure routes : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Test Type : Human repeat insult patch test (HRIPT)

Exposure routes : Skin contact Result : negative

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Test Type : Local lymph node assay (LLNA)

Exposure routes : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

1,1'-(p-tolylimino)dipropan-2-ol:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

1,4-Naphthoquinone:

Assessment : Probability or evidence of skin sensitisation in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Vinyltoluene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Test Type: Chromosome aberration test in vitro

Result: negative

Methacrylic acid, monoester with propane-1,2-diol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: positive

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 489

Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version **Revision Date:** SDS Number: Date of last issue: 27.06.2024 07.01.2025 10680008-00016 Date of first issue: 18.04.2013 19.0

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Vinyltoluene:

Species Rat

Application Route inhalation (vapour)

Exposure time 103 weeks Result : negative

Methacrylic acid, monoester with propane-1,2-diol:

Species Rat

Application Route Ingestion Exposure time 2 Years Result negative

Remarks Based on data from similar materials

Reproductive toxicity

Not classified based on available information.

Components:

Tetramethylene dimethacrylate:

Effects on fertility Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Test Type: Embryo-foetal development

Result: negative

Vinyltoluene:

Effects on foetal develop-

ment

Species: Rat

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Methacrylic acid, monoester with propane-1,2-diol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

Remarks: Based on data from similar materials

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: Ingestion Method: OECD Test Guideline 414

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

1,1'-(p-tolylimino)dipropan-2-ol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion
Method: OECD Test Guideline 422

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Vinyltoluene:

Assessment : May cause respiratory irritation.

Methacrylic acid, monoester with propane-1,2-diol:

Assessment : May cause respiratory irritation.

1,4-Naphthoquinone:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Quartz (SiO2):

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Lungs

Assessment : Shown to produce significant health effects in animals at con-

centrations of 0.02 mg/l/6h/d or less.

Repeated dose toxicity

Components:

Tetramethylene dimethacrylate:

Species : Rat
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 33 Days

Method : OECD Test Guideline 422

Quartz (SiO2):

Species : Humans LOAEL : 0,053 mg/m3 Application Route : Inhalation

Remarks : This substance(s) is not bioavailable and therefore does not

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

contribute to a dust inhalation hazard.

Methacrylic acid, monoester with propane-1,2-diol:

Species : Rat
NOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 54 Days

Method : OECD Test Guideline 422

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Species : Rat, male
NOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 13 Weeks

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Species : Rat, female
NOAEL : 100 mg/kg
LOAEL : 300 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Components:

Vinyltoluene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version **Revision Date:** SDS Number: Date of last issue: 27.06.2024 07.01.2025 10680008-00016 Date of first issue: 18.04.2013 19.0

SECTION 12: Ecological information

12.1 Toxicity

Components:

Tetramethylene dimethacrylate:

Toxicity to fish EC50 (Leuciscus idus (Golden orfe)): 32,5 mg/l

> Exposure time: 48 h Method: DIN 38412

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC10 (Desmodesmus subspicatus (green algae)): 4,35 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 9,79 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EC10: 7,51 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Vinyltoluene:

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 9,3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): 0,319 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 0,25 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox- : 1

icity)

Toxicity to microorganisms NOEC (activated sludge): 170 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Quartz (SiO2):

LC50 (Danio rerio (zebra fish)): 508 mg/l Toxicity to fish

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 731 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version **Revision Date:** SDS Number: Date of last issue: 27.06.2024 07.01.2025 10680008-00016 Date of first issue: 18.04.2013 19.0

aquatic invertebrates Exposure time: 48 h

Remarks: Based on data from similar materials

Methacrylic acid, monoester with propane-1,2-diol:

Toxicity to fish LC50 (Leuciscus idus (Golden orfe)): 493 mg/l

> Exposure time: 48 h Method: DIN 38412

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 143 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Raphidocelis subcapitata (freshwater green alga)): >

97,2 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Raphidocelis subcapitata (freshwater green alga)): >=

97.2 ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 45,2 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 1,55 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,46 mg/l

Exposure time: 48 h

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 7,49

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,56

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,7 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

1,1'-(p-tolylimino)dipropan-2-ol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 17 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 28,8 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Desmodesmus subspicatus (green algae)): 57,8 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

ErC50 (Desmodesmus subspicatus (green algae)): 245 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC10 : > 1.995 mg/l

Exposure time: 30 min

1,4-Naphthoquinone:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): 0,045 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50: 0,026 mg/l Exposure time: 48 h

Toxicity to algae/aquatic : NOEC : 0,07 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

plants Exposure time: 72 h

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic : 1

toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : M-factor: 10

Chronic aquatic toxicity : M-factor: 1

12.2 Persistence and degradability

Components:

Tetramethylene dimethacrylate:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 28 d

Method: OECD Test Guideline 310

Vinyltoluene:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 36,7 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Methacrylic acid, monoester with propane-1,2-diol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 81 % Exposure time: 28 d

Method: OECD Test Guideline 301C

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Biodegradability : Result: rapidly biodegradable

Biodegradation: 70,73 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1,5 % Exposure time: 29 d

Method: OECD Test Guideline 301B

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

1,1'-(p-tolylimino)dipropan-2-ol:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 90,1 % Exposure time: 60 d

Method: OECD Test Guideline 301B

1,4-Naphthoquinone:

Biodegradability : Biodegradation: 39 %

Exposure time: 5 d

12.3 Bioaccumulative potential

Components:

Tetramethylene dimethacrylate:

Partition coefficient: n-

octanol/water

: log Pow: 3,1

Vinyltoluene:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): < 500

Remarks: Based on data from similar materials

Partition coefficient: n- :

octanol/water

log Pow: 3,44

Remarks: Calculation

Methacrylic acid, monoester with propane-1,2-diol:

Partition coefficient: n-

octanol/water

log Pow: 0,97

1-Isopropyl-2,2-dimethyltrimethylene diisobutyrate:

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1.130 - 1.200

Method: OECD Test Guideline 305

Partition coefficient: n- :

octanol/water

log Pow: 4,91

Remarks: Calculation

Reaction mass of 2-{[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino}ethanol and 2,2'-[(4-methylphenyl)imino]diethanol:

Partition coefficient: n- : log Pow: 2,17

octanol/water Method: OECD Test Guideline 117

1,1'-(p-tolylimino)dipropan-2-ol:

Partition coefficient: n-

: log Pow: 2,1

octanol/water

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

1,4-Naphthoquinone:

Partition coefficient: n- : log Pow: 1,77

octanol/water Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09*, waste adhesives and sealants containing organic

solvents or other hazardous substances

unused product

08 04 09*, waste adhesives and sealants containing organic

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

solvents or other hazardous substances

uncleaned packagings

15 01 10*, packaging containing residues of or contaminated

by hazardous substances

Acc. Packaging Act properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA (Passenger) : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or

not

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: Number on list 75: If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

Not applicable

Regulation (EU) No 2024/590 on substances that de-

Not applicable

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast)

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

Not applicable

(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version Revision Date: SDS Number: Date of last issue: 27.06.2024 19.0 07.01.2025 10680008-00016 Date of first issue: 18.04.2013

Water hazard class (Germa-

ny)

: WGK 3 highly hazardous to water

Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : 5.2.1: Total dust:

Not applicable

5.2.2: Inorganic substances in powdered form:

Not applicable

5.2.4: Inorganic substances in gaseous form:

Not applicable

5.2.5: Organic Substances:

Not applicable

5.2.7.1.1: Carcinogenic substance:

Not applicable

5.2.7.1.1: Quartz fine dust PM4: others: 1,76 % Quartz (SiO2) 5.2.7.1.1: Formaldehyde:

Not applicable 5.2.7.1.1: fibres: Not applicable

5.2.7.2: Poorly degradable, easily enrichable and highly toxic

organic substances: Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,8 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H226 : Flammable liquid and vapour.

H300 : Fatal if swallowed. H301 : Toxic if swallowed. H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways. H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

Version 19.0	Revision Date: 07.01.2025		Number: 30008-00016	Date of last issue: 27.06.2024 Date of first issue: 18.04.2013
H318 H319 H330		: Causes serious eye dar: Causes serious eye irrit: Fatal if inhaled.		eye irritation.
H335 H361d		: May cause respiratory irritation.: Suspected of damaging the unborn child.		
H372 H400		Causes damage to organs through prolonged or repeated exposure if inhaled.Very toxic to aquatic life.		ed.
H410 H411 H412		: \\ :	Very toxic to aqu Foxic to aquatic l	atic life with long lasting effects. ife with long lasting effects. Ic life with long lasting effects.
				3 3

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Corr. : Skin corrosion

Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

2004/37/EC : Europe. Directive 2004/37/EC on the protection of workers

from the risks related to exposure to carcinogens or mutagens

at work

DE DFG MAK : Germany. MAK BAT Annex IIa

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

2004/37/EC / TWA : Long term exposure limit

DE DFG MAK / MAK : MAK value

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



BASIC WIT-PM 200 - 300 ML (A)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.06.2024

 19.0
 07.01.2025
 10680008-00016
 Date of first issue: 18.04.2013

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sheet

Sources of key data used to compile the Safety Data

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Skin Sens. 1 H317 Calculation method Aquatic Chronic 3 H412 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN